

SINCE 1978



# Product Datasheet

LEADING LIGHT

vkleadinglight.gr

Core

## VK/04715/PE/D/B/W/63


Black. 3000K. 25W. 4x338lm. AC200-240V. 36°. Led Bridgelux 3030.  
Ceiling/pendant. < 45°C. 50.000hrs. Dimmable Yes, Triac. CRI>90.  
Aluminum. IP20




IP20



### Dimensions



### Gallery





### Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	25W
Voltage	AC200-240V
Extra	AOHUA Triac Dimming (D111) 12-24W, AC:200-240V, DC:30-40V,560mA
Fitting	Pendant
Type	Light
Safety class	
Light source	Bridgelux
IP Rating	<b>IP20</b>
CRI	CRI>90
Dimmable	 TRIAC
Lifetime	50.000hrs
Cable Length	155cm (max)
Working temperature	<45°C
PAGE	58 New Products 2026
NICKNAME	Core

Physical Specifications	
Family	Core
Color	Black
Material	Aluminum
Width	62.8cm
Length	62.8cm
Height	1.8cm (+155cm of cable)
Width (inner box)	710cm
Length (inner box)	710cm
Height (inner box)	150cm

Illumination Data	
Lumen	1352lm (4x338lm)
Beam angle	36°
Lighting direction	

Packing Info	
Pcs/carton	1pc

Certification & Warranty	
Guarantee	3 years