

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Aura

VK/04691/PE/D/RGD/W




Rose Gold. 3000K. 20W. 1958lm. AC220-240V. Up70°, Down45°. Led Bridgelux COB. Driver KGP. Ceiling/pendant. -20°C → 45°C. 50.000hrs. Clicks 20.000. Dimmable Yes, Triac. CRI>90. Aluminum+glass. IP20

IP20



Dimensions



Gallery





Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	20W
Voltage	AC220-240V
Fitting	Pendant
Type	Light
Safety class	
Light source	Bridgelux COB
IP Rating	IP20
CRI	CRI>90
Dimmable	 TRIAC
Lifetime	50.000hrs
Clicks	20,000
Driver	KGP
Cable Length	300cm (max)
Working temperature	-20°C-45°C
PAGE	76 New Products 2026
NICKNAME	Aura

Physical Specifications	
Family	Aura
Color	Rose Gold
Material	Aluminum+Glass
Width	13.5cm
Length	13.5cm
Height	9.9cm (+300cm of cable)
Net weight of product (kg)	1.80kg
Gross weight with inner box (kg)	2.50kg
Width (inner box)	20.4cm
Length (inner box)	37.1cm
Height (inner box)	13.4cm

Illumination Data	
Lumen	1958lm
Beam angle	Up70° Down45°
Lighting direction	

Packing Info	
Pcs/carton	4pcs

Certification & Warranty	
Guarantee	2 years