

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Lip

VK/02283/AN/W


Anthracite. 3000K. 5.5W. 400lm. AC220-240V. LED CREE 1304. 82°. 30.000hrs. Adjustable 320° (body) & 335° (base). Dimmable No. -20°C→45°C. Outdoor floor. CRI>80. 30cm. Die-casting aluminum+Glass. IP65




IP65




Dimensions



Gallery






Downloads




VK Leading Light

Since 1978

Technical Specifications	
Kelvin	3000K
Power	5.5W
Voltage	AC220-240V
Fitting	Outdoor floor
Type	Light
Safety class	
Light source	CREE 1304
IP Rating	IP65
CRI	CRI>80
Dimmable	
Lifetime	30.000hrs
Clicks	25,000
Working temperature	-20°C-45°C
PAGE	334 New Products 2026
NICKNAME	Lip

Physical Specifications	
Adjustable	 Adjustable
Rotation	320° & 335°
Family	Lip
Color	Anthracite
Material	Die-casting aluminum + glass
Width	6.3cm
Length	ø4.4cm
Height	30cm
Net weight of product (kg)	0.48kg
Gross weight with inner box (kg)	0.52kg
Width (inner box)	11.5cm
Length (inner box)	13cm
Height (inner box)	34cm

Illumination Data

Lumen	400lm
Beam angle	82°
Lighting direction	

Packing Info

Pcs/carton	6pcs
------------	------

Certification & Warranty

Guarantee	3 years
-----------	---------


Energy Label



VK LEADING LIGHT
VK/02283/AN/W

A
B
C
D
E
F
G

7 kWh/1000h



2019/2015