

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Coko

VK/04612/2/W-B/WW

Recessed adjustable spot led. 2700K. 1.114lm. 2x6W. CRI>90, IP20, White
+ black



IP20

Dimensions	Gallery	Downloads
	Recessed Downlights Led Coko	

Technical Specifications	
Kelvin	2700K
Power	2x6W
Voltage	220-240V
Fitting	Recessed ceiling
Type	Downlight LED
Safety class	
Light source	Bridgelux
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	<45°C
PAGE	177 Technical 2024
NICKNAME	Coko

Physical Specifications	
Adjustable	
Recessed ceiling	Yes
Rotation	Orizontal 355°, Vertical 90°
Color	White+Black
Material	Aluminium+PMMA lens
Width	3.5cm
Length	12.5cm
Height	7.3cm
Net weight of product (kg)	0.41
Gross weight with inner box (kg)	0.43
Gross weight with master box (kg)	9
Cut out	10x3.5cm
Width (inner box)	12cm
Length (inner box)	15cm
Height (inner box)	5.2cm

Illumination Data	
Lumen	1.114lm
Beam angle	24°
Lighting direction	

Packing Info	
Pcs/carton	20pcs

Certification & Warranty	
Guarantee	5 years

Energy Label



VK LEADING LIGHT

VK/04612/2/W-B/WW

A

B

C

D

E

F

G

12

kWh/1000h



2019/2015