

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

Habi

VK/04339/W/W

Recessed spot led, 2W, 3000K, 180lm, 8°, IP20, white



IP20



Dimensions	Gallery	Downloads																																																																																								
5.7 cm 6.8 cm 6.8 cm Cut hole 6 cm 5.7 cm	Recessed Dark-SquareLight Led Habi <table><tr><th>Model</th><th>Power (W)</th><th>Beam Angle (°)</th><th>Color Temp (K)</th><th>Life (h)</th><th>IP</th><th>Dimmable</th><th>Notes</th></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr><tr><td>VK/04339/W/W</td><td>2</td><td>8</td><td>3000</td><td>50000</td><td>IP20</td><td>Yes</td><td>Recessed Dark-SquareLight Led</td></tr></table>	Model	Power (W)	Beam Angle (°)	Color Temp (K)	Life (h)	IP	Dimmable	Notes	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led	
Model	Power (W)	Beam Angle (°)	Color Temp (K)	Life (h)	IP	Dimmable	Notes																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			
VK/04339/W/W	2	8	3000	50000	IP20	Yes	Recessed Dark-SquareLight Led																																																																																			

Technical Specifications	
Kelvin	3000K
Power	2W
Voltage	100-240V
Fitting	Recessed ceiling
Type	Dark Downlight LED
Safety class	
Light source	OSRAM
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	< 45°C
PAGE	186 Technical 2024
NICKNAME	Habi

Physical Specifications	
Recessed ceiling	Yes
Color	White sand
Material	Aluminium
Width	ø6.8cm
Length	ø6.8cm
Height	5.7cm
Net weight of product (kg)	0.18
Gross weight with inner box (kg)	0.21
Gross weight with master box (kg)	7.08
Cut out	ø6cm depth 5.7cm

Illumination Data	
Lumen	180lm
Beam angle	8°
Lighting direction	
Dark light	Yes

Packing Info	
Pcs/carton	30pcs

Certification & Warranty	
Guarantee	3 years

Energy Label



VK LEADING LIGHT
VK/04339/W/W

A

B

C

D

E

F

G

2

kWh/1000h



2019/2015