

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr

San



VK/04616/W/W

Recessed dark downlight led. 3000K. 1.508lm. 12W. 15° CRI>90, IP20, White



IP20



Dimensions	Gallery	Downloads
	 	  

Technical Specifications	
Kelvin	3000K
Power	12W
Voltage	220-240V
Fitting	Recessed dark ceiling
Type	Downlight LED
Safety class	
Light source	Bridgelux
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	50.000hrs
Working temperature	<45°C
PAGE	188 Technical 2024
NICKNAME	San

Physical Specifications	
Recessed ceiling	Yes
Color	White
Material	Aluminium+PMMA lens
Width	ø8.25cm
Length	ø8.25cm
Height	7.4cm
Net weight of product (kg)	0.22
Gross weight with inner box (kg)	0.26
Gross weight with master box (kg)	12.9
Cut out	ø7.5cm
Width (inner box)	10.5cm
Length (inner box)	11.5cm
Height (inner box)	8.5cm

Illumination Data	
Lumen	1.508lm
Beam angle	15°
Lighting direction	
Dark light	Yes

Packing Info	
Pcs/carton	48pcs

Certification & Warranty	
Guarantee	5 years

Energy Label



VK LEADING LIGHT
VK/04616/W/W

A

B

C

D

E

F

G

E

12
kWh/1000h



2019/2015